

F5

Global Radio System



G.R.S. MODEL F5

Komunikace ve výbušných atmosférách

- Bluetooth.
- Dotykový displej.
- M3d Priorita.
- Vestavn3e GPS.
- Funkce opakování.
- Propojen3 s WI-FI s3t3.
- Dlouh3 3ivotnost baterie.
- Opera3n3 s3st3m Android.
- SOS t3s3nov3e tla33tko.
- AUX konektor pro p33slu3enstv3.
- V3bu3n3e atmosféry ATEX.
- Skupinov3e a individu3ln3 vol3n3 z termin3lu.
- Mo3nost instalace extern3ch aplikac3.
- Propojen3 mezi GRS a analogov3mi s3st3my.



Z3kladn3 technick3 3daje

Rozm3ry	62 (3) x 32 (H) x 140 (D) mm	CPU	SDM450-B; Qualcomm® Core 8 p3i 1.8 GHz, v3robn3 technologi3 14 nm; Adreno™ 506 GPU; podpora kodeku H.265 p3i rozli3en3 1080p @ 60 FPS.
V3ha	300 g	Ulo3i3t3	RAM 3GB ROM 32GB TrasFlash karta 128 GB
V3hody	<ul style="list-style-type: none">• LTE 3irok3e p3sma + 33zk3e p3sma (DMR 4W).• Video kodek H.265• Nahr3v3n3 vide3 ve tm3e pomoc3 infra p33sv3tu.• Vysok3 p3esnost ur3en3 polohy.• Velmi v3konn3e sv3tlo (CREE Xp-g3 LED 6W; p3i 350mA sv3t3vost 205 lm/W, p3i 2A sv3t3vost 863 lm; hlin3kov3e ochrann3e pouzdro).	Geolokace	GPS, GLONASS, Galileo / A-GPS
Standard	<ul style="list-style-type: none">• V3konn3a sign3lov3a ant3na• Provozn3 teplota -20 3C a3 +50 3C• Skladovac3 teplota -40 3C a3 +70 3C• Norma odolnosti IP-69 / MIL-STD-810G	FM	Podporov3no, je pot3eba venkovn3i ant3na, nebo pou3it jako ant3nu sluch3tk3.
Voliteln3 certifik3t3	UN38.3 / MSDSIP-69 / CCC / CTA / ROHS / Reach / Ex ib IIB T4 / Ex ib IIC T4 / Ex ib D21 T130 nap3. pro Z3nu 1 a Z3nu 2	S3t'	EU, Asie
OS	Origin3l Android Q 10.0; podpora customizace a dal33ho v3voje , nab3z3me SDK, mo3nost instalace aplikac3 t3et3ch stran.	Komunika3n3 frekvence	GSM B2 / B3 / B5 / B8 FDD-LTE B1 / B2 / B3 / B5 / B7 / B8 / B18/ B19 / B20 / B25 / B26 / B28a / B28b TDD-LTE B34 / B38 / B39 / B40 / B41 4W DMR 400 ~ 480 MHz CDMA BC0 WCDMA B1 / B2 / B5 / B8
Displej	4" LCD 4.0 IPS; QHD; 540 x 1080 px	Dv3 SIM karty	LTE + GSM
P3edn3 kamera	800W 8mp, FF, mo3nost rozpozn3n3 obli3eje.	Mo3nosti osazen3 SIM	A) nanoSIM + nanoSIM B) nanoSIM + TrasFlash karta s velikost3 128 GB C) nanoSIM + TrasFlash 128 GB s podporou 33frov3n3
Zadn3 kamera	1080p @ 60 FPS; 5 Mpix; 33irokouhln3a 3o3ka; podpora infra viditeln3st3 v noci. 400 ~ 480 MHz; 136 ~ 174 MHz; 220 ~ 260 MHz; 350 ~ 390 MHz; 12.5 kHz; 25 kHz;		
4W DMR modul	Podporuje 400 ~ 480 MHz UHF, VHF; Optim3ln3 frekvence 136 ~ 174 MHz; 220 ~ 260 MHz; 350 ~ 390 MHz; Frekvencn3 intervaly digital 12.5 kHz; analog 12.5 kHz, 25 kHz.		



SCANLOCK CZ, spol. s r.o.
B3ezinova 1608/42
616 00 Brno
Czech Republic

Phone +420 515 917 917
E-mail info@scanlock.cz
www scanlock.cz/grs

